TEETER WORKS' LED WALL WASHER SERIES

MEGA SERIES

Project:	Type:
Prepared By:	Date:

DESCRIPTION

- Super narrow optic design
- Maximum projecting distance of 650 ft at minimum 4.5 degree beam angle
- DMX512 control
- Available in RGB and RGBW
- Multiple beam angles: 4.5, 10, 25, 40, and 60
- High strength die-cast aluminum construction
- Easy installation with adjustable bracket
- Shock resistant, IP67 waterproof rated
- Logarithmic dimming technology
- ETL

SPECIFICATIONS

Item #	Color	Peak Wave Length	Quantity	Power Consumption(W)	Beam Angle	Dimensions	Input Voltage	Working Voltage	Water-proof
RF5-M-280-C XX	Red	620nm	126	300	10°/25° 40°/60° Optional	28.89"(L)x15.51"(W)x4.76"(H)	AC100-277V	DC24V	IP67
	Green	520nm							
	Blue	465nm							
	White	2700K-6500K							
RF5-M-600C XX	Red	620nm	252	600	10°/25° 40°/60° Optional	30.78"(L)x27.83"(W)x10.23"(H)	AC100-277V	DC24V	IP67
	Green	520nm							
	Blue	465nm							
	White	2700K-6500K							
RF5-M-160-C XX	Red	620nm	66	160	4.5°	28.89"(L)x15.51"(W)x4.76"(H)	AC100-277V	DC24V	IP67
	Green	520nm							
	Blue	465nm							
	White	2700K-6500K							
RF5-M-320-C XX	Red	620nm	132	320	4.5°	30.78"(L)x27.83"(W)x10.23"(H)	AC100-277V	DC24V	IP67
	Green	520nm							
	Blue	465nm							
	White	2700K-6500K							

Teeter Works: 3497 All American Blvd. Orlando, Florida 32810 TEL: 407 637 7260 Email: eran@teeterworks.com